

No guarantee can be given in respect of this translation in all cases the latest German-language version of this standard shall be taken as authoritative

## Sealing Push-in Caps

DIN


443

## Verschlußdeckel zum Eindrücken


Dimensions in mm

▽ Range 2 DIN 3141


Type A conical



Type B cylindrical



recommended receiving hole



Prior to insertion of the sealing cap the hole should, if necessary, be given an application of sealing compound.

Designation of a sealing cap (Type A or B at manufacturer's choice) of nominal diameter  $d = 25$  mm, rust-protected by phosphating (phr):

Sealing cap 25 DIN 443 - phr

If a specific type is required, the appropriate type letter symbol must be stated in the designation, e.g.:

Sealing cap A 25 DIN 443 - phr

$d$	$h$	$r_1$	$r_2$	$s$	Weight (7,85 kg/dm <sup>3</sup> ) kg/1000 pieces ≈
zc10	js 16				
8	3	20	1	0,75	0,72
(9)	3	22	1	0,75	0,84
10	3	25	1	0,75	0,97
(11)	4	28	1	1	1,9
12	4	30	1	1	2
(13)	4	32	1	1	2,15
14	5	35	1	1	2,98
(15)	5	38	1	1	3,2
16	5	40	1	1	3,55
(17)	5	42	1	1	3,9
18	6	45	1	1	4,83
(19)	6	48	1	1	5,1
20	6	50	1	1	5,55
(21)	7	52	1,6	1,6	10,2
22	7	55	1,6	1,6	10,8
(24)	7	60	1,6	1,6	12,3
25	8	60	1,6	1,6	14,3

$d$	$h$	$r_1$	$r_2$	$s$	Weight (7,85 kg/dm <sup>3</sup> ) kg/1000 pieces ≈
zc10	js17				
(26)	8	65	1,6	1,6	15
28	9	70	1,6	1,6	18,2
(29)	9	70	1,6	1,6	19,1
(30)	9	75	1,6	1,6	20
(32)	10	80	1,6	1,6	23,7
(34)	10	85	1,6	1,6	25,7
36	11	90	1,6	1,6	29,9
(38)	12	95	1,6	1,6	34,4
40	12	100	1,6	1,6	36,7
(42)	13	105	1,6	1,6	41,7
45	14	110	1,6	1,6	48,3
(48)	15	120	1,6	1,6	55,6
50	15	125	1,6	1,6	58,6
(52)	16	130	2,5	2	79
56	17	140	2,5	2	91,2
(60)	18	150	2,5	2	104
63	19	160	2,5	2	116

Bracketed sizes should be avoided where possible.

Material: USt 1303 according to DIN 1623 or St 3 according to DIN 1624 (at manufacturer's choice)

Other materials by agreement

Finish: regular

phr = rust-protected by phosphating according to DIN 50942

electrolytically deposited surface protection according to DIN 267 Sheet 9

Nachdruck, auch auszugsweise, nur mit Genehmigung des Deutschen Normenausschusses, Berlin 30, gestattet.

Translation  
Fachtechnisches Übersetzungsinstitut  
Henry G. Freeman, Düsseldorf